

- Industrial design
- High durability
- Brushless motor
- Plug & play



| Model | Bit drive | Torque range min - max [lb in] | Torque range min - max [cNm] | Free speed r/min | Weight kg | Weight lbs | Ordering No. |
|------------|-----------------|--------------------------------|------------------------------|------------------|-----------|------------|--------------|
| S8020 | 1/4" Hex | 0,26-1,7 | 3-20 | 700-1000 | 0,46 | 1,01 | 4221000273 |
| S8020-WS | Wing shank 4 mm | 0,26-1,7 | 3-20 | 700-1000 | 0,46 | 1,01 | 4221000272 |
| S8050 | 1/4" Hex | 0,43-4,3 | 5-50 | 700-1000 | 0,46 | 1,01 | 4221000274 |
| S8120 | 1/4" Hex | 1,3-10,4 | 15-120 | 700-1000 | 0,46 | 1,01 | 4221000275 |
| S8120-2000 | 1/4" Hex | 1,3-10,4 | 15-120 | 1400-2000 | 0,46 | 1,01 | 4221000276 |
| S8160 | 1/4" Hex | 1,7-13,9 | 20-160 | 700-1000 | 0,46 | 1,01 | 4221000277 |
| S8200 | 1/4" Hex | 3,5-17,4 | 40-200 | 700-1000 | 0,46 | 1,01 | 4221000278 |
| S8250 | 1/4" Hex | 4,3-21,7 | 50-250 | 500-750 | 0,46 | 1,01 | 4221000279 |

Power supply

| | | | |
|-------|------|------|------------|
| EBS D | 0,38 | 0,84 | 4221000280 |
|-------|------|------|------------|

NOTE. Power Supply needs to be ordered separately